

LED Lighting Solutions

The future of illumination



LED-8-A-TD100S

Energy Efficient Street and Area Lighting

New for 2008

FEATURES

- UL® LISTED
- Heat dissipation using advanced aerospace technology
- Weight's only : **12 lbs 3 oz**
- IP65 Classified
- High efficient LEDs
- Environmentally friendly
- Lifespan >50,000 hrs



- **Voltage Input:**
Standard = 21VDC 4.9Amps
Optional = AC
- **Color Temperature:**
Standard = 6500K
Other colors temp. available
- **Power consumption:**
103 W
- **Dimensions & weight :**
23" X 10" X 5" 12lb 3oz

APPLICATIONS

- Streets
- Highways
- Bridges
- Parking Lots
- Biking/walking Trails
- Outbuildings
- Athletic Fields

	LED-8-A-TD100S-W1		LED-8-A-TD100S-W2	
Lum. Flux	> 5000		> 6000	
Color Temp	6500K		6500K	
Height	Illumination (Ft Candle)	Coverage Area	Illumination (Ft Candle)	Coverage Area
23'	2.9	124' (φ)	4.3	124' (φ)
26'	2.3	144' (φ)	3.3	144' (φ)
29'	1.8	164' (φ)	2.6	164' (φ)
33'	1.4	180' (φ)	2.1	180' (φ)
36'	1.1	196' (φ)	1.8	196' (φ)
39'	0.9	216' (φ)	1.5	216' (φ)

LED-8-A-TD100S installation



Specifications and dimension subject to change. Please contact us for latest information.



Ledimation, Inc.

2035 Royal Lane, Suite 200

Dallas, Texas 75229

Phone 972.955.9990

Fax 214.241.0916

www.ledimation.com